Kontakt-Simon S.A.
43-500 Czechowice-Dziedzice, ul. Bestwińska 21
tel.: 32 32 46 300, faks: 32 32 46 331
e-mail: info@kontakt-simon.com.pl
www.kontakt-simon.com.pl



BMD1.01/43

Bell Button, (module), 10AX, quick connection, Silver matt, metalic

Series	Simon Basic
Product name / Type	Bell Button
Color	Silver matt, metalic
Product type	module
Nominal current	10 AX
Nominal voltage	250 V
Connection type / Crimp type	quick connection
IP degree of protection	IP20/IP44
Notes	IP44 splash proof only with IP44 Neos frame: BMRC1B/..; BMRC2B/... or IP44 Standard frame: BMR1B/..; BMR2B/...; BMR3B/..
Backlight,	Optional, Not included

ETIM Class	EC000029 Push button
In print/Pictogram	symbol "bell"
Type of material	Plastic, PC, Halogen free
Surface protection	varnished
Type of curface	matt
Mounting method[ETIM]	flush mounted
Fixing method	claws / screws
Height of product	75 mm
Width of product	75 mm
Depth of product	41 mm
Installation depth	24 mm
Operating method / Way of operating	rocker button
Number of buttons / levers	1
Connection layout	Single button
Model	Single push button
Number of poles	1
Connectors - operating	Single normally open connector (NO)

Outer carton quantity	10
Measure unit	Qty.
Individual packaging EAN code	5902787837358
Pack. type	foil
Ind. pack. height	16 cm
Ind. pack. width	11 cm
Individual packaging lenght	4.5 cm
Weight of individual packaging with product	0.073 kg
Outer type	cardboard box
Height of outer	10 cm
Outer width	19 cm
Outer lenght	23 cm