



## 0620211-100

Electric vehicle charging station, Simon Neon, pedestal, 3-phase, 32A, 44kW, 2 socket outlets Type 2, RFID, MID, 40A, C type circuit breaker 30mA, A type earth leakage circuit breaker

|                         |                                   |                          |                                                                         |                               |               |
|-------------------------|-----------------------------------|--------------------------|-------------------------------------------------------------------------|-------------------------------|---------------|
| Series                  | Simon Neon                        | Mounting method[ETIM]    | pedestal                                                                | Individual packaging EAN code | 8421053310380 |
| Product name / Type     | electric vehicle charging station | Height of product        | 1390 mm                                                                 | Indiv. weight                 | 36 kg         |
| Nominal voltage         | 400 V                             | Width of product         | 330 mm                                                                  |                               |               |
| IP degree of protection | IP54                              | Depth of product         | 180 mm                                                                  |                               |               |
| Voltage source          | 3-phase, 32A                      | ETIM Class               | EC002883 Charging device for electric vehicles                          |                               |               |
| Charging current        | 32 A                              | Use                      | Public areas                                                            |                               |               |
| Type of station         | free-standing                     | IK mechanical resistance | IK10                                                                    |                               |               |
| Charging power          | 22-44 kW                          | Protection               | 40A, C type circuit breaker, 30mA, A type earth leakage circuit breaker |                               |               |
| compatible with         | OCPP                              |                          |                                                                         |                               |               |
| Maximum charging power  | 44000 W                           |                          |                                                                         |                               |               |
| Access control          | RFID                              |                          |                                                                         |                               |               |