Kontakt-Simon S.A.
43-500 Czechowice-Dziedzice, ul. Bestwińska 21
tel.: 32 32 46 300, faks: 32 32 46 331
e-mail: info@kontakt-simon.com.pl
www.kontakt-simon.com.pl

KFH216U/72

Floor box insert, inox steel, IP66, IK08, 2.5×K45, 2 sockets type F (schuko), 2 modules RJ45 cat. 6 UTP, easy access lock

Series	KGT
Product name / Type	Floor box insert
Color	inox steel
Nominal current	16 A
Nominal voltage	250 V
IP degree of protection	IP66
Notes	Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.
Numer of modules	2.5
Module type	K45
Number of K45 modules	2.5 × K45
Heat resistance	+ 125 ° C in accordance with IEC 60695-10-2
Material flammability	+ 850 ° C / 30 sec. (GWFI in accordance with IEC 60670
Maximum load of a closed box	2000 kg
Maximum load of an open box	250 kg
Module type	K45 (45x45mm), K45/2 (45×22,5mm)

Type of material	Metal, polycarbonate
ETIM Class	EC000024 Installation box for underfloor-installation
Features	2 sockets type F (schuko), 2 modules RJ45 cat. 6 UTP, easy access lock
Model	with earthing, Schuko
Shape	Rectangular
IK mechanical resistance	IK08

Outer carton quantity	1
Measure unit	Qty.
Individual packaging EAN code	8421053334911
Indiv. weight	0.702 kg