



## KFH221/74

Floor box insert, black, IP66, IK08, 2.5×K45, 2 sockets type E (pin), module 22,5x45mm with 2 Keyston latch for RJ45 or multimedia connectors, easy access lock

Series	KGT	Type of material	Metal, polycarbonate	Outer carton quantity	1
Product name / Type	Floor box insert	ETIM Class	EC000024 Installation box for underfloor-installation	Measure unit	Qty.
Color	black	Features	2 sockets type E (pin), module 22,5x45mm with 2 Keyston latch for RJ45 or multimedia connectors, easy access lock	Individual packaging EAN code	8421053335000
Nominal current	16 A	Model	with earthing, Pin earthing	Indiv. weight	0.682 kg
Nominal voltage	250 V	Shape	Rectangular		
IP degree of protection	IP66	IK mechanical resistance	IK08		
Notes	Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.				
Numer of modules	2.5				
Module type	K45				
Number of K45 modules	2.5 × K45				
Heat resistance	+ 125 ° C in accordance with IEC 60695-10-2				
Material flammability	+ 850 ° C / 30 sec. (GWFI in accordance with IEC 60670				
Maximum load of a closed box	2000 kg				
Maximum load of an open box	250 kg				
Module type	K45 (45x45mm), K45/2 (45x22,5mm)				