



KFH225USEC/72

Floor box insert, inox steel, IP66, IK08, 2.5×K45, 2 sockets type E (pin), 2 modules RJ45 cat. 5e UTP, allen key lock

| | | | | | |
|------------------------------|--|--------------------------|--|-------------------------------|---------------|
| Series | KGT | Type of material | Metal, polycarbonate | Outer carton quantity | 1 |
| Product name / Type | Floor box insert | ETIM Class | EC000024 Installation box for underfloor-installation | Measure unit | Qty. |
| Color | inox steel | Features | 2 sockets type E (pin), 2 modules RJ45 cat. 5e UTP, allen key lock | Individual packaging EAN code | 8421053335031 |
| Nominal current | 16 A | Model | with earthing, Pin earthing | Indiv. weight | 0.704 kg |
| Nominal voltage | 250 V | Shape | Rectangular | | |
| IP degree of protection | IP66 | IK mechanical resistance | IK08 | | |
| Notes | Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine. | | | | |
| Numer of modules | 2.5 | | | | |
| Module type | K45 | | | | |
| Number of K45 modules | 2.5 × K45 | | | | |
| Heat resistance | + 125 ° C in accordance with IEC 60695-10-2 | | | | |
| Material flammability | + 850 ° C / 30 sec. (GWFI in accordance with IEC 60670) | | | | |
| Maximum load of a closed box | 2000 kg | | | | |
| Maximum load of an open box | 250 kg | | | | |
| Module type | K45 (45x45mm), K45/2 (45x22,5mm) | | | | |