



## KFH136U/74

Made-to-order product, Floor box insert, KGT, IP66, 16A, black, IK08

Status of Product	made-to-order product	Type of material	Metal, polycarbonate	Outer carton quantity	1
Series	KGT	ETIM Class	EC000024 Installation box for underfloor-installation	Measure unit	Qty.
Product name / Type	Floor box insert	Features	socket type P40 (italian), module RJ45 cat. 6 UTP, easy access lock	Individual packaging EAN code	8421053333099
Color	black	Model	type P40 (italian standard)	Indiv. weight	0.384 kg
Nominal current	16 A	Shape	Square		
Nominal voltage	250 V	IK mechanical resistance	IK08		
IP degree of protection	IP66				
Notes	Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.				
Numer of modules	1.5				
Module type	K45				
Number of K45 modules	1.5 × K45				
Heat resistance	+ 125 ° C in accordance with IEC 60695-10-2				
Material flammability	+ 850 ° C / 30 sec. (GWFI in accordance with IEC 60670				
Maximum load of a closed box	1500 kg				
Maximum load of an open box	250 kg				
Module type	K45 (45x45mm), K45/2 (45x22,5mm)				