



## KFH140SEC/74

Made-to-order product, Floor box insert, KGT, IP66, 16A, black, IK08

|                              |  |                          |  |                               |              |
|------------------------------|--|--------------------------|--|-------------------------------|--------------|
| Status of Product            | made-to-order product  | Type of material         | Metal, polycarbonate   | Outer carton quantity         | 1            |
| Series                       | KGT  | ETIM Class               | EC000024 Installation box for underfloor-installation            | Measure unit                  | Qty.         |
| Product name / Type          | Floor box insert   | Features                 | socket type G (british), allen key lock, blind element 22,5x45mm | Individual packaging EAN code | 842105333150 |
| Color                        | black  | Model                    | type G (british standard)  | Indiv. weight                 | 0.383 kg     |
| Nominal current              | 16 A   | Shape                    | Square   |                               |              |
| Nominal voltage              | 250 V  | IK mechanical resistance | IK08   |                               |              |
| IP degree of protection      | IP66   |                          |  |                               |              |
| Notes                        | Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine. |                          |  |                               |              |
| Numer of modules             | 1.5  |                          |  |                               |              |
| Module type                  | K45  |                          |  |                               |              |
| Number of K45 modules        | 1.5 × K45  |                          |  |                               |              |
| Heat resistance              | + 125 ° C in accordance with IEC 60695-10-2  |                          |  |                               |              |
| Material flammability        | + 850 ° C / 30 sec. (GWFI in accordance with IEC 60670   |                          |  |                               |              |
| Maximum load of a closed box | 1500 kg  |                          |  |                               |              |
| Maximum load of an open box  | 250 kg   |                          |  |                               |              |
| Module type                  | K45 (45x45mm), K45/2 (45x22,5mm)   |                          |  |                               |              |