



KFH145U/72

Made-to-order product, Floor box insert, KGT, IP66, 16A, inox steel, IK08

| | | | | | |
|------------------------------|--|--------------------------|--|-------------------------------|---------------|
| Status of Product | made-to-order product | Type of material | Metal, polycarbonate | Outer carton quantity | 1 |
| Series | KGT | ETIM Class | EC000024 Installation box for underfloor-installation | Measure unit | Qty. |
| Product name / Type | Floor box insert | Features | socket type G (british), module RJ45 cat. 5e UTP, easy access lock | Individual packaging EAN code | 8421053333167 |
| Color | inox steel | Model | type G (british standard) | Indiv. weight | 0.385 kg |
| Nominal current | 16 A | Shape | Square | | |
| Nominal voltage | 250 V | IK mechanical resistance | IK08 | | |
| IP degree of protection | IP66 | | | | |
| Notes | Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine. | | | | |
| Numer of modules | 1.5 | | | | |
| Module type | K45 | | | | |
| Number of K45 modules | 1.5 × K45 | | | | |
| Heat resistance | + 125 ° C in accordance with IEC 60695-10-2 | | | | |
| Material flammability | + 850 ° C / 30 sec. (GWFI in accordance with IEC 60670 | | | | |
| Maximum load of a closed box | 1500 kg | | | | |
| Maximum load of an open box | 250 kg | | | | |
| Module type | K45 (45x45mm), K45/2 (45x22,5mm) | | | | |