



NPR1.01E/49

Single break push button with pictogras, (module),
Simon 24, IP20/IP44, 10AX, 10A, black matt

| | | | | | |
|------------------------------|---|-------------------------------------|---------------------------------------|---|---------------|
| Series | Simon 24 | ETIM Class | EC000029 Push button | Outer carton quantity | 10 |
| Product name / Type | single break push button with pictogras | In print/Pictogram | none | Measure unit | Qty. |
| Color | black matt | Type of material | Plastic, PC, Halogen free | Individual packaging EAN code | 5902787908829 |
| RAL (akin) | RAL 9004 | Surface protection | varnished | Pack. type | foil |
| Product type | module | Type of surface | matt | Ind. pack. height | 16 cm |
| Nominal current | 10 A | Mounting method[ETIM] | flush mounted | Ind. pack. width | 11 cm |
| Nominal current | 10 AX | Fixing method | claws / screws | Individual packaging length | 4.5 cm |
| Nominal voltage | 250 V | Height of product | 76.3 mm | Weight of individual packaging with product | 0.0485 kg |
| Connection type / Crimp type | quick connection | Width of product | 76.3 mm | Outer type | cardboard box |
| IP degree of protection | IP20/IP44 | Depth of product | 40 mm | Height of outer | 10 cm |
| Notes | To obtain IP44 splash-proof class an additional frame seal required | Installation depth | 28.6 mm | Outer width | 19 cm |
| | | Operating method / Way of operating | rocker button | Outer length | 23 cm |
| | | Number of buttons / levers | 1 | | |
| | | Connection layout | Single button | | |
| | | Model | Single push button | | |
| | | Number of poles | 1 | | |
| | | Connectors - operating | Single normally closed connector (NC) | | |
| | | Product length | 4 cm | | |