



BMW2.01/21

Two-pole switch, (module), 10AX, quick connection, Inox, metallized

Series	Simon Basic
Product name / Type	two-pole switch
Color	Inox, metallized
Product type	module
Nominal current	10 AX
Nominal voltage	250 V
Connection type / Crimp type	quick connection
IP degree of protection	IP20/IP44
Notes	IP44 splash proof only with IP44 Neos frame: BMRC1B/...; BMRC2B/... or IP44 Standard frame: BMR1B/...; BMR2B/...; BMR3B/... IP44 splash proofness after applying BMR1B; BMR2B; BMR3B frames
Backlight,	Optional, Not included

ETIM Class	EC001590 Switch
In print/Pictogram	symbol "0-1"
Type of material	Plastic, PC, Halogen free
Surface protection	varnished
Type of surface	mat
Mounting method[ETIM]	flush mounted
Fixing method	claws / screws
Height of product	75 mm
Width of product	75 mm
Depth of product	41 mm
Installation depth	24 mm
Operating method / Way of operating	rocker button
Number of buttons / levers	1
Connection layout	Two-pole switch
Number of poles	2
Connectors - operating	Two normally open connectors (NO)

Outer carton quantity	10
Measure unit	Qty.
Individual packaging EAN code	5902787819736
Pack. type	foil
Ind. pack. height	16 cm
Ind. pack. width	11 cm
Individual packaging length	4.5 cm
Weight of individual packaging with product	0.0789 kg
Outer type	cardboard box
Height of outer	10 cm
Outer width	19 cm
Outer length	23 cm